

BVE 6-02X 6-way splitter | 9.5 dB | 5 ... 1800 MHz | housing design 02



- ✓ Suitable for DOCSIS 3.1 and 4.0
- ✓ Class A (+10 dB) according to EN 50083-2
- ✓ Inputs and outputs hum-suppressed
- ✓ High intermodulation suppression
- ✓ High return loss and isolation
- ✓ Vodafone listed

Order information

| | |
|--------------------------|---------------|
| Type | BVE 6-02X |
| Order no. | BVE00602X |
| GTIN | 7611682009705 |
| PE | 1 |
| VE | 1 |
| EU customs tariff number | 85291080 |



Technical data

| | |
|-------------------------------------|--|
| Frequency range | 5 ... 1800 MHz |
| Screening factor acc. to EN 50083-2 | Class A + 10 dB |
| Surge Protection | 1 kV @ 1.2/50 µs surge voltage according to IEC 61000-4-5 / 160 Vdc impulse and UM TS 41 |
| Intermodulation ratio (EN 60728-4) | < -115 dBc @ 120 dBµV |
| Splitting | 6-way |
| Distribution | |
| Distribution loss | 9.0 ±0.3 dB @ 10 MHz 8.9 ±0.2 dB @ 65 MHz 8.8 ±0.2 dB @ 108 MHz 8.8 ±0.3 dB @ 204 MHz 8.8 ±0.3 dB @ 258 MHz 9.0 ±0.4 dB @ 470 MHz 9.0 ±0.5 dB @ 862 MHz 9.5 ±0.6 dB @ 1218 MHz 11.0 ±0.9 dB @ 1794 MHz |
| RF connectors | |
| Type | F-Buchse (IEC 61169-24) |
| Isolation | |
| Out-Out | > 35 dB @ 10 ... 204 MHz > 28 dB @ 204 ... 862 MHz > 27 dB @ 862 ... 1218 MHz > 25 dB @ 1218 ... 1794 MHz |
| Connectors | |
| Connector type | F female (IEC 61169-24) |
| Impedance | 75 Ohm |
| Return loss | > 25 dB @ 10 ... 204 MHz > 20 dB @ 204 ... 862 MHz > 17 dB @ 862 ... 1218 MHz > 16 dB @ 1218 ... 1794 MHz |
| General | |
| Operating temperature range | -15 °C ... +60 °C |
| Dimensions (W × H × D) appr. | 89 x 39 x 54 mm |
| IP code | IP67 |