

## OPTRX 4 MICRO



Optical TV SAT receiver with universal legacy 4SAT+TV+FM outputs, SC/APC optical connector

		OPTRX 4 MICRO
Code		270662
Optical input		1 SC/APC
Outputs		4 SAT (HL,VL,HH,VH) + 1 TV
<b>Optical input</b>		
Connector		SC/APC
WaveLenght	nm	1290-1580
Optical return loss	dB	>45
Max optical input power	dB	-8
<b>RF Outputs</b>		
Frequency band	MHz	87-862/950-2150
Connectors	Type	F female
Return loss	dB	-10
Output level TV		
-8dBmo(40Mux)	dBμV	78
-8dBmo(16Mux)	dBμV	82
-8dBmo(8Mux)	dBμV	85
-14dBmo(40Mux)	dBμV	68

-14dBmo(16Mux)	dB $\mu$ V	72
-14dBmo(8Mux)	dB $\mu$ V	75
<b>Output level SAT</b>		
-8dBmo	dB $\mu$ V	82
-14dBmo	dB $\mu$ V	70
<b>Features</b>		
Power supply	Vac/Hz	
Consumption	W	2.5
Current consumption	mA, V	180, 12
Power supply	V	14/18 on all outputs
Operating temperature	$^{\circ}$ C	-5 - +50
Leds	dB $\mu$ V	Power status green LED
Standard conformity		2014/53/UE, 2011/65/UE
Dimensions	mm	120x100x30